

Single Channel Gas Monitor (HS-1000M-W1)



HS-1000M-W1 is an wall-mounted single channel gas monitor with an alarm sounder and light for fixed gas detector. It is designed with 4-digit big 7-segment LED and 4 alarm LEDs, big waring light and buzzer.

Visual and audible indication will keep workers safe along with self-diagnosis function.

FEATURES

- ✓ Wall-mounting type
- ✓ 4-digit 7-segment LED
- ✓ 4 Alarms type (AL1, AL2, AL3, fault)
- ✓ Buzzer, LED Lamp
- ✓ 4-20mA, alarm relay, RS-485 Modbus output
- ✓ Alarm delay setup available
- ✓ IP65 grade
- ✓ Non-explosion proof type

기술 규격

| | |
|-----------------------|--|
| Detectable gas | O2, CO, H2S, NO2, SO2, H2, LEL, etc... |
| Display | 4 digit 7-segment high bright LED, 4xLEDs (AL1, AL2, AL3, Fault) |
| Display size | 80(W)x28(H)mm |
| Detection range | User selectable (0000 to 9999) |
| Input signal | 4-20mA full scale (Power consumption 24 VDC 200mA) |
| Output | 2-wire DC 4~20mA, 4 x relay contact (250 VAC/5A), RS-485 Modbus |
| Alarm | AL1, AL2, AL3, Fault |
| Alarm display | 4xLEDs (AL1, AL2, AL3, Fault), Buzzer(100dB@1m), Warning Light |
| Power | 110 or 220 VAC (user select by switch), 50~60Hz |
| Dimension | 213(W)x185(H)x119(D)mm, 318mm(H) with warning light |
| Weight | 1.73Kg |
| Housing material | ABS, IP65 |
| Operating Temperature | -20 ~ +50°C |
| Cable | Standard CVVS 14 AWG to 24A WG |
| Function | Alarm delay, Buzzer Stop, Reset, Display calibration |

